



## HYBRID FOIL ADHESIVE

## Product Information Bulletin

## Recommended Parameters

### HYBRID FOIL ADHESIVE

It is a water base printing adhesive where used to achieve an elastic, soft touching and foil covering effect in textile printing.

#### Highlights

- ▶ If under the advised conditions is fixed, wash fastness is high
- ▶ It is provide easily to use during printing
- ▶ Maximum brightness, excellent elasticity and high fastness.
- ▶ Also works as "inline" foil adhesive

#### Printing Tips

- ▶ It has been manufactured for foil printing
- ▶ It is provide to adhesion foil to fabric that it increases wash strenght of fabric
- ▶ It is advised to try on suitable conditions.

#### Compliance

- ▶ Suitable to ecological standards.
- ▶ For Ecological Certifications, please visit [www.inknovators.com](http://www.inknovators.com)

#### Precautions

- ▶ Never use water to reduce the viscosity.
- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ After using, the screen should be cleaned with water and sponge.
- ▶ Soluble in water.
- ▶ It is packed in 30kg and 60kg blue polyethylene cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: [info@inknovators.com](mailto:info@inknovators.com)

#### Mesh

Counts: 55 mesh



#### Squeegee

Durometer: 50-60 Shore  
U type dr. blade



#### Cure Temperatures

320°F(150°C) for 1 minute  
280°F(140°C) for 1,5 minutes



#### Additives

Do not use any additives  
that are not advised



#### Shipping & Storage

41°F - 86°F (5°C - 30°C)



#### Press & Clean Up

**Clean up:** Water  
**Hand Press:** 320-350°F at 4-6 bars pressure  
in 10-15 second  
**Continuous Press:** 320-350°F at 4-6 bars  
pressure 15-25 seconds



#### Health & Safety

Please see: Safety Data Sheet

