

HYBRID ANTIMIGRATION BASE 02 Product Information Bulletin

HYBRID ANTIMIGRATION BASE 02

It is a water based barrier printing base.

Highlights

- ► It is prevent to contaminate base color's to print.
- Lt has extremely wash fastness.
- ▶ It provides to elastic and migration barrier on dark colored

Printing Tips

 It is used for prevent to contaminate prints of polyester fabric & reactive printing fabric

Compliance

- Suitable to ecological standards.
- For Ecological Certifications, please visit www.inknovators.com

Precautions

- ► Before usage, please stir the product well. Do not use any additives that are not advised.
- Soluble in water.
- ► It is packed in 30kg and 60kg blue polyethylene cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ► Email: info@inknovators.com

Recommended Parameters

Fabric Types

For 100% Poly, Sublimation and Polyester Blend Fabrics



Mesh

Counts: 37-43 mesh



Squeegee

Durometer: 55-60 Shore U type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes 280°F(140°C) for 2 minutes It can be fixed under room temperature



Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Water and sponge



Health & Safety

Please see: Safety Data Sheet

