

HYBRID LT PUFF BASE

It is a water based printing base used to achieve soft touching effect in textile printing. It is colored with pigments.

Highlights

- ▶ It is possible to obtain proper & intumescent surface with Hybrid LT Puff Base
- ▶ There are two types intumescent paste as low & high temperature
- ▶ It is fixed under the advised conditions.
- ▶ Hybrid LT Puff Base has extremely wash fastness.
- ▶ Elastic and soft-handfeel suede puff effect

Printing Tips

- ▶ It has been manufactured for intumescent printings

Compliance

- ▶ Suitable to ecological standards.
- ▶ For Ecological Certifications, please visit www.inknovators.com

Precautions

- ▶ Never use water to reduce the viscosity.
- ▶ Before usage, please stir Hybrid LT Puff Base well. Do not use any additives that are not advised.
- ▶ After using, the screen should be cleaned with water and sponge.
- ▶ Soluble in water.
- ▶ It is packed in 30kg and 60kg blue polyethylene cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Mesh

Counts: 55 mesh



Squeegee

Durometer: 50-60 Shore
U type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes
280°F(140°C) for 2 minutes



Additives

Do not use any additives
that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Use only water to clean



Health & Safety

Please see: Safety Data Sheet

