



HYBRID THICKENER

Product Information Bulletin

Recommended Parameters

HYBRID THICKENER

Thickener



Highlights

- ▶ It viscosity capability is perfect even if small quantities therefore it should be tried in pastes.
- ▶ It protects to alive of pigments.
- ▶ Suitable to ecological standards.
- ▶ It provides to raise of viscosity of print paste and liquids which has pH 7 and above

Shipping & Storage

41°F - 86°F (5°C - 30°C)



inknovators



Precautions

- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ Never use water to reduce the viscosity.
- ▶ After using, the silk-screen should be cleaned with water.
- ▶ It is packed in 5kg, 30kg, 60kg and 120kg plastic cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Health & Safety

Please see: Safety Data Sheet



HYBRID THICKENER