



PL FOIL ADHESIVE

Product Information Bulletin

Recommended Parameters

PL FOIL ADHESIVE

It is a phthalate free printing base used to adhesive where used to achieve an elastic, soft touching and foil covering effect in textile printing.

Highlights

- ▶ If under the advised conditions is fixed, wash fastness is high
- ▶ It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- ▶ It provide easily to use during printing
- ▶ Excellent plastisol floc printings with high washing fastness.

Printing Tips

- ▶ It has been manufactured for foil printing.

Compliance

- ▶ It is not suitable to ecological standards due to containing PVC.

Precautions

- ▶ Never use water to reduce to viscosity.
- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ After using, the silk-screen should be cleaned with water.
- ▶ It is provide to adhesion foil to fabric that it increases wash strenght of fabric.
- ▶ It is packed in 10kg cans.
- ▶ It can be mixed with PL pigments and PL White in any ratio.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Mesh

Counts:34-55 mesh



Squeegee

Durometer: 60-80 Shore
V type dr. blade



Press&Cure Temperatures

320°F(160°C) for 1.5 minutes
Hand press: 320-350°F at 4-6 bar pressure in 7-10 second
Continuous press:320-350°F at 4-6 bar pressure in 15-25 second



Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Use water to clean



Health & Safety

Please see: Safety Data Sheet

