

PL MIXING BASE

Product Information Bulletin

PL MIXING BASE

It is a phthalate free printing base used to achieve elastic and soft touching opaque effect in textile printing.

🕮 Highlights

- ► It has elastic and opaque cover effect.
- ► It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- ► It use for making colors with plastisol pigments.
- At the same time pigment able to add into mixing base and obtained plastisol colors.
- ► It provides dropped and non-slipped property to sock base.

Printing Tips

It has been manufactured for obtain to opaque cover transparent effect.

Compliance

It is not suitable to ecological standards due to containing PVC.

Precautions

- Lt use for making colors with plastisol pigments.
- After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- ► It is packed in 5kg,10kg and 20kg plastic cans.
- ► It can be mixed with PL pigments and PL White in any ratio
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Recommended Parameters

Counts: 43-120 mes



Squeegee

Durometer: 60-80 Shore V type dr. blade



Cure Temperatures



Additives



Do not use any additives that are not advised



41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet

