

PL PUFF BASE

It is a phthalate free printing base used to achieve an elastic and soft touching puffing effect in textile printing. It can be used as a transparent or can be coloured with PL colors.

Highlights

- There are different types which puffed at low and high temperature. It provides to elastic and soft-handfeel suede plastisol puff
- It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- It achieve very smooth puffed surface with it.
- It has high wash fastness.

Printing Tips

- It has been manufactured for puffed prints.

Compliance

- It is not suitable to ecological standards due to containing PVC.

Precautions

- Never use water to reduce viscosity.
- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- It is packed in 10kg cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Mesh

Counts: 34-43 T mesh



Squeegee

Durometer: 60-80 Shore
V type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes



Additives

Do not use any additives
that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or
Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet

