

### PL CMYK YELLOW

#### **Product Information Bulletin**

### PL CMYK YELLOW

It is a phthalate free plastisol based printing CMYK pigment base used to achieve colored printing effect with elastic covering and soft touching prosperties in textile printing

# <u>lll</u> Highlights

- Lt is easily fixed on the machine.
- ▶ It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- ► The requested color can be easily made with this product.
- ► It provides color productivity and elasticity on print.

# Printing Tips

It has been manufactured for plastisol colors

## Compliance

It is not suitable to ecological standards due to containing PVC.

### Precautions

- ► Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- ► It is packed in 10kg cans.
- ▶ It can be mixed with PL Clear Base and PL White in any ratio.
- Fluorescent colors can be used to make alive colors.
- ► The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help
- ► In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ► The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ► Email: info@inknovators.com

# Recommended Parameters

Counts: 43-120 mesh



Saueeaee

Durometer: 60-80 Shore V type dr. blade



**Cure Temperatures** 

320°F(160°C) for 1.5 minutes



Additives



Do not use any additives that are not advised

In order to reduce the viscosity, up to 3% of PL Reducer can be added into it



**Shipping & Storage** 

41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet

